

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE  
Serial Number: 09/944,993  
Filing Date: August 30, 2001  
Title: BIT INVERSION IN MEMORY DEVICES

Page 2  
Dkt: 703.155US1

### IN THE CLAIMS

Please amend the claims as follows.

1. (Currently Amended) A method of transferring a data stream comprising:  
transferring a plurality of bits associated with a data stream from a data source to a temporary storage, ~~wherein the data source is designated as the data source based upon the operation being performed, and wherein the data source with other operations can be classified as a target data source;~~  
concurrently intercepting during the transfer and on or within the data source, each bit associated with the data stream and counting a bit-transfer total and a bit-set total associated with the data stream; and  
determining on or within the data source, if the bit-set total exceeds more than half the bit-transfer total and if so setting an inversion flag bit which is associated with the data stream.
2. (Original) The method of claim 1, further comprising:  
transferring from the temporary storage to a target source each bit associated with the data stream and concurrently inverting each bit as transferred, if the inversion flag bit is set.
3. (Original) The method of claim 1, further comprising:  
shifting the inversion flag bit to a flag storage.
4. (Original) The method of claim 3, further comprising:  
assembling one or more additional inversion flag bits in the flag storage, each additional inversion flag bit associated with a single additional data stream; and  
maintaining each additional data stream in the temporary storage.

31 Avenue

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE  
Serial Number: 09/944,993  
Filing Date: August 30, 2001  
Title: BIT INVERSION IN MEMORY DEVICES

Page 3  
Dkt: 703.155US1

5. (Original) The method of claim 4, further comprising:  
transferring from the temporary storage to a target source each bit associated with the data stream and each of the additional data streams while concurrently inverting each transferred bit, if the inversion flag bit associated with a transferred data stream is set, as identified in the flag storage.
6. (Original) The method of claim 5, wherein the flag storage is a register.
7. (Currently Amended) A method of transferring a data stream, comprising:  
receiving a data stream and an inversion flag associated with the data stream from a data source, wherein a classification of the data source is transitory and can be modified to a target data source depending upon an operation being performed;  
transferring one or more bits associated with the data stream from a data source to a target source, if the inversion flag is unset; and  
inverting, on or within the data source, the bits associated with the data stream as the data stream is transferred from the data source to the target source, if the inversion flag is set.
8. (Original) The method of claim 7, wherein the inversion flag and the data stream are stored together in the data source.
9. (Original) The method of claim 7, wherein the inversion flag and the data stream are separately stored in the data source.
10. (Original) The method of claim 7, wherein the inversion flag is stored with one or more additional inversion flags as a single data structure in the data source, each additional inversion flag associated with an additional data stream.
11. (Currently Amended) A computer readable medium having executable instructions for executing a method which is operable to invert transferred data, the method comprising:

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE  
Serial Number: 09/944,993  
Filing Date: August 30, 2001  
Title: BIT INVERSION IN MEMORY DEVICES

Page 4  
Dkt: 703.155US1

acquiring a data stream and an inversion flag from a data source, ~~wherein the data source can also be a target data source depending upon an operation being performed;~~

separating, on or within the data source, the data stream and the inversion flag into a data stream storage and an inversion flag storage; and

buffering, on or within the data source, one or more additional data streams and one or more additional inversion flags from the data source in the storages.

12. (Original) The medium of claim 11, further comprising:

inverting all bits associated with a transferred data stream as the transferred data stream is sent to a target source from the data stream storage, if a corresponding inversion flag associated with the transferred data stream is set in the inversion flag storage.

13. (Currently Amended) A data structure implemented in a computer readable medium operable to be transferred from a data source, comprising:

a data stream having a plurality of bits; and

an inversion bit associated with the data stream which is set after the data stream is transferred to a temporary storage, the inversion bit is set by a data source if a total number of set data stream bits exceeds more than half a total number of bits associated with the data stream, wherein the total numbers are tabulated concurrently as the data stream is transferred to the temporary storage within or on the data source, and wherein if the inversion bit is set then a state within the data source is changed permitting the data stream to be inverted when transferred from the data source to a target source, and wherein the data stream is adapted to be received from a data source and a classification of the data source is dependent upon an operation being performed, and wherein with other operations the data source may be classified as a target data source that is a recipient of the data stream and the inversion bit.

14. (Previously Presented) The data structure of claim 13, further comprising:

an inversion bit stream including the inversion bit and one or more additional inversion bits, each additional inversion bit associated with an additional data stream.

## AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 – EXPEDITED PROCEDURE

Serial Number: 09/944,993

Filing Date: August 30, 2001

Title: BIT INVERSION IN MEMORY DEVICES

Page 5

Dkt: 703.155US1

15. (Currently Amended) The data structure of claim 14, wherein the data stream and the additional data streams are transferred from the temporary storage to ~~[[a]] the~~ target source, and wherein during the transfer the transferred bits associated with the transferred data stream are inverted if a corresponding inversion bit or additional inversion bit associated with the transferred data stream is set.

16. (Currently Amended) The data structure of claim 13, wherein the bits of the data stream are inverted if the inversion bit is set during a transfer of the data stream from the temporary storage to ~~[[a]] the~~ target source.

17. (Currently Amended) An inversion data transfer system, comprising:  
a data source device including a temporary storage and a controller  
~~[[a]] the~~ temporary storage; and  
~~[[a]] the~~ controller that transfers a data stream having a plurality of bits from the data source device to the temporary storage, and concurrent to the transfer determines if a total number of set bits within the data stream is more than half of a total number of bits associated with the data stream, and if so associating a set inversion bit with the data stream, otherwise associating an unset inversion bit with the data stream, ~~and wherein the data source can also be classified as a target data source when it receives the data stream.~~

18. (Original) The system of claim 17, further comprising:  
a target source device which concurrently receives the bits of the data stream inverted, as the data stream is transferred from the temporary storage, if a set inversion bit associated with the data stream is detected.

19. (Original) The system of claim 17, further comprising:  
a register storage operable to house the inversion bit and one or more additional inversion bits, wherein each additional inversion bit is associated with an additional data stream.

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 – EXPEDITED PROCEDURE  
Serial Number: 09/944,993  
Filing Date: August 30, 2001  
Title: BIT INVERSION IN MEMORY DEVICES

Page 6  
Dkt: 703.155US1

20. (Original) The system of claim 19, wherein the controller further retrieves from the register storage each inversion bit associated with a transferred data stream and is operable to concurrently transfer the transferred data stream from the temporary storage and invert the bits associated with the transferred data stream if the inversion bit is set.
21. (Currently Amended) An inversion data transfer system, comprising:  
a data source device, ~~wherein the classification of the data source device is transitory and can change, based on operations being performed, into a target source device;~~  
the a target source device; and  
a controller included within the data source device that acquires a data stream and an inversion bit associated with the data stream from the data source device and inverts bits associated with the data stream during a transfer of the data stream to a target source device, if the inversion bit is set.
22. (Original) The system of claim 21 further comprising:  
a temporary storage operable to house the data stream as the data stream is acquired from the data source device; and  
a register storage operable to house the inversion bit as the data stream is acquired from the data source device.
23. (Previously Presented) The system of claim 21, wherein the controller acquires the inversion bit by stripping the inversion bit from the data stream.
24. (Original) The system of claim 21, wherein the controller acquires the inversion bit as a separate data structure having one or more additional inversion bits with each additional inversion bit being associated with a single additional data stream.
25. (Currently Amended) A system for transferring a data stream, comprising:  
a control buffer;  
a storage buffer;

AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE  
Serial Number: 09/944,993  
Filing Date: August 30, 2001  
Title: BIT INVERSION IN MEMORY DEVICES

Page 7  
Dkt: 703.155US1

an inversion storage;

a counting set of executable instructions operable to count set bits associated with a data stream being received from the control buffer into the storage buffer as the storage buffer receives the data stream from a data source and a designation of the data source is determined based on an operation that delivers the data stream to the storage buffer and wherein other operations can designate the data source as a target data source that receives the data stream, and the counting set of executable instructions further operable to generate generates an inversion bit associated with the data stream, wherein the inversion bit is housed in the inversion storage and is set if a total number of set bits exceeds more than half a total number of bits associated with the data stream, and wherein the counting set of executable instructions, the control buffer, the inversion storage, and the storage buffer are included within the data source.

26. (Original) The system of claim 25, further comprising:

a transfer set of executable instructions operable to use the counting set of executable instructions to transfer the data stream from the storage buffer to a target device, wherein the entire data stream is inverted if the inversion bit is set as the data stream is being transferred to the target device.

27. (Original) The system of claim 26, wherein the inversion bit is transferred with the data stream to the target device.

28. (Currently Amended) A memory apparatus, comprising:

a controller that acquires a data packet and an associated inversion bit and ~~is operable to transfer~~ transfers the packet and concurrently ~~invert~~ inverts the packet if the inversion bit is set, wherein the data packet and the controller reside on or within a data source.

29. (Original) The apparatus of claim 28, wherein the controller buffers the packet prior to transfer.

## AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 – EXPEDITED PROCEDURE

Page 8

Serial Number: 09/944,993

Dkt: 703.155US1

Filing Date: August 30, 2001

Title: BIT INVERSION IN MEMORY DEVICES

30. (Original) The apparatus of claim 29, wherein the controller separates the packet and the inversion bit.

31. (Original) The apparatus of claim 30, wherein the inversion bit is housed in a register prior to the transfer.

32. (Original) The apparatus of claim 28, wherein the controller acquires the inversion bit by counting set bits associated with the data packet, as the packet is acquired.

33. (Currently Amended) A memory apparatus, comprising:  
an inversion bit;  
a data packet;  
a state machine that controls the transfer of the data packet to a target device wherein the packet is inverted as it is transferred to the target device, if the inversion bit is set, and wherein the data packet and the state machine reside within a data source which serves as the apparatus, ~~and wherein a designation of the target device is transitory and resolved based on an operation being performed and with other operations the target device can also be a data source device.~~

34. (Original) The apparatus of claim 33, further comprising:  
a buffer to house the data packet prior to transfer to the target device; and  
a register to house the inversion bit.

35. (Original) The apparatus of claim 33, wherein the state machine is configured by interfacing one or more electro-mechanical devices.

36. (Original) The apparatus of claim 33, wherein the state machine is configured using a set of executable instructions.

37. (Original) The apparatus of claim 33, wherein the data packet is a fixed length data packet.

## AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 – EXPEDITED PROCEDURE

Serial Number: 09/944,993

Filing Date: August 30, 2001

Title: BIT INVERSION IN MEMORY DEVICES

Page 9

Dkt: 703.155US1

38. (Original) The apparatus of claim 33, wherein the data packet is a variable length data packet.

39. (Original) The apparatus of claim 33, wherein the apparatus is a flash memory device.

40. (Currently Amended) A flash memory device, comprising:

a temporary storage;

a receiving controller;

a counting controller; and

a transferring controller that transfers a data packet received by the receiving controller in a temporary storage to a target device and further inverts the data packet during the transfer if the counting controller indicates to the transferring controller that the packet requires inversion, and wherein the temporary storage, the receiving controller, the counting controller, and the transferring controller reside within or on a data source which is the flash memory device ~~the data packet is initially received from a data source and a designation of the data source is transitory based on an operation being performed and with other operations the data source can also be designated as the target device.~~

41. (Original) The flash memory device of claim 40, wherein the counting controller indicates the packet requires inversion if a total number of set bits associated with the packet exceeds more than half a total number of bits associated with the packet.

42. (Original) The flash memory device of claim 40, wherein the memory device is at least one of a compact flash memory card and a multimedia card.

43. (Original) The flash memory device of claim 40, wherein the memory device is included in the operation of a at least one of a digital camera device, digital video device, and a portable audio player device.



## AMENDMENT AND RESPONSE UNDER 37 CFR § 1.116 - EXPEDITED PROCEDURE

Serial Number: 09/944,993

Filing Date: August 30, 2001

Title: BIT INVERSION IN MEMORY DEVICES

Page 10

Dkt: 703.155US1

44. (Original) The flash memory device of claim 40, wherein the counting controller includes a packet based ones counter.
45. (Original) The flash memory device of claim 40, further comprising a shift-load register used to house an inversion bit generated by the counting controller, wherein the inversion bit, if set, indicates the data packet is to be inverted.
46. (Original) The flash memory device of claim 45, wherein one or more multiplexers, the shift-load register, and the temporary storage are used by the transferring controller to transfer the data packet.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS .
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**